

## SK-APU Drill Chuck

### Brief introduction

SK-APU DRILL CHUCK TOOL HOLDER, Application range: clip diameter: 0.5-16mm bit .Mechanical spindle and cutting tools and other accessories.High Precision SK shank Tool Holder ,balanced G6.3 or G2.5 For choose.

SK Tool Holders for mechanical spindle and cutting tool and other accessory tool connection. Is a simple, popular spindle shank connection standard, mainly SK30 SK40 SK50... Etc.. Mold industry, and high-speed engraving machine, used more.

### Specification:

1. material:20CrMnTi
2. hardness:56±2HRC
3. taper tolerance less than AT3
4. carbon depth >0.8
5. High precision shank connection

Model	Chucking Dia	C	D	L	L1	Weight (KG S)
SK40-APU8-85	0.3-8	42	63.55	85	150.4	0.85
SK40-APU13-100	1-13	54	63.55	100	165.4	1
SK40-APU16-100	3-16	62	63.55	100	165.4	1.1
SK50-APU8-90	0.3-8	42	97.5	90	191.8	1.3
SK50-APU13-100	1-13	54	97.5	100	201.8	1.4
SK50-APU16-105	3-16	62	97.5	105	206.8	1.5



Order No	Model	Clamping Range	D	L	Weight (KGS)
22300880A	SK30-APU08-80	1-8	37	80	0.6
223013120A	SK30-APU13-120	1-13	50	120	1.45
223016120A	SK30-APU16-120	3-16	57	120	1.78
22400875A	SK40-APU08-75	1-8	37	75	1.46
224013100A	SK40-APU13-100	1-13	50	100	2
224016105A	SK40-APU16-105	3-16	57	105	2.33
22500875A	SK50-APU08-75	1-8	37	75	3.86
225013100A	SK50-APU13-100	1-13	50	100	4.4
225016105A	SK50-APU16-105	3-16	57	105	4.73
应用范围：夹持直径为0.5-16mm的钻头					